

Platformlift model PRAKTIKUS HP

Capacity 400 kg,
platform height max. 1200 mm

For the occasional, internal application of lifting and transporting of goods.

Features

- Easy lifting by tiltable foot pedal.
- Lowering speed can be finely metered for sensitive lowering of the load.
- Ergonomic handlebar for easy operation.
- Steering roller with brake for safe parking of the hand stacker.
- Robust construction with chrome plated chassis, hard chromium plated piston and pressure relief valve.
- Covered chain deflection for increased safety.



Technical data model PRAKTIKUS HP

Model	HP 0485	HP 0412
Art.-No.	040008778	040008779
Capacity, kg	400	400
Platform height max. $h_3 + h_{13}$, mm	850	1200
Platform height min. h_{13} , mm	200	200
Free lift h_2 , mm	650	1000
Stroke h_3 , mm	650	1000
Lifting height per pump stroke, mm	23	23
Overall height h_1 , mm	960	1310
Overall length L_1 , mm	1037	1037
Overall width b_1 , mm	590	590
Platform length P_1 , mm	650	650
Platform width P_2 , mm	550	550
Tyre type ¹	VG/VG	VG/VG
Steering rollers, mm	150x45	150x45
Load rollers, mm	150x45	150x45
Number of wheels/load rollers	2/2	2/2
Ground clearance m_1 , mm	50	50
Wheelbase y , mm	785	785
Weight, kg	66	71

¹VG ... Solid rubber

