



TRALIFT™ TE – PALAN ÉLECTRIQUE À CHAÎNE

Le treuil Tralift™ TE est un palan motorisé à chaîne. Il est utilisé pour lever des charges. Il peut être utilisé à poste fixe, sur une potence, sous un pont roulant, ou accroché à un chariot motorisé ou non. L'appareil est commandé par une boîte à boutons. En option, il peut recevoir une radio commande.

PALAN ELECTRIQUE A CHAINE Tralift™ TE 125KG à 2000kg

- Fin de course haut et bas
- Commande très basse tension
- Arrêt d'urgence
- Limiteur de charge à friction
- Tension d'alimentation 230V ou 400V 50Hz-60Hz 3 phases

Données techniques :

| Model | Number of falls | Load chain Dia. x pitch (mm) | Lifting speed (m/min) | Hoisting motor power (kW) | Hoist weight lift 3 m (kg) | Hoist headroom (mm) | Trolley speed (m/min) | Trolley motor power (kW) | Hoist/trolley weight | | | Beam adjustment min/max (mm) |
|-----------------------|-----------------|------------------------------|-----------------------|---------------------------|----------------------------|---------------------|--------------------------------------|--------------------------|----------------------|-------------------------------|-------------------------|------------------------------|
| | | | | | | | | | push type (kg) | dual type ⁽¹⁾ (kg) | electric type (kg) | |
| TE125 125 kg | 1 | 4 x 12 | 10 10/3.3 | 0.3 0.3/0.13 | 24 | 330 | Single | - | 3,5 | - | - | 50 to 220 or 221 to 300 |
| TE250 250 kg | 1 | 5 x 15 | 8 8/2.7 | 0.4 0.4/0.13 | 30 | 340 | speed | - | 3,5 | - | - | |
| TE500 500 kg | 2 | 5 x 15 | 4 4/1.3 | 0.4 0.4/0.13 | 33 | 430 | 5 or 10 | 0.18 | 8,5 | - | 50 | |
| TE500 500 kg | 1 | 6.3 x 19 | 8 8/2.7 | 0.9 0.9/0.13 | 38 | 400 | 20 | 0.25 | 8,5 | - | 55 | |
| TE1000 1000 kg | 2 | 6.3 x 19 | 4 4/1.3 | 0.9 0.9/0.13 | 41 | 480 | dual speed 9 and 3 or 0.18/0.6 | 10,5 10,5 18 | 19 | 60 | 58 to 220 or 221 to 300 | |
| TE1000 1000 kg | 1 | 8 x 24 | 6,3 6.3/1.9 | 1,6 1.6/0.55 | 58 | 490 | | | 19 | 73 | 66 to 220 or 220 to 300 | |
| TE2000 2000 kg | 2 | 8 x 24 | 3,15 3.15/0.8 | 1,6 1.6/0.55 | 62 | 580 | | | 22,5 ⁽¹⁾ | 89 | | |

(1) - The weight includes operating chain (loop 3 m)

(2) - Not standard cross bar